



BIGGER SNOW REMOVAL FOR SMALLER VEHICLES.

The clearing power of Arctic plows meets the new breed of agile, down-sized 4x4s. Featuring a scaled-down version of the QUIK*LINK® mounting system, a high density polyethylene skin and standard, sturdy Arctic construction, the Arctic LD-P offers many of the features of its bigger Arctic brothers. They'll call you small – until they call you for help.

HOT-DIPPED GALVANIZED STEEL FRAME

provides added resistance to abrasion, water and rust, making our plows virtually maintenance free

5 LASER-CUT, STEEL REINFORCING RIBS back our frictionless poly moldboard with the strength of steel

1/4" SLICK POLYETHYLENE MOLDBOARD

throws snow further and faster resulting in less resistance and vehicle wear, and improved fuel economy

6" DEFLECTOR/ **EXTENDER**

TURIN

keeps snow down in front of blade or adds height to the plow for deeper snow



OPTIONAL EXTRA SPRING KIT



OPTIONAL SHOE KIT

3" DIAMETER TENSION SPRINGS support the plow and are attached to

a 1/4"-thick boxed quadrant that fixes to a double leg 2" X 2" boxed tubing A-frame with a 1" easy-to-remove greasable and bushed king bolt

1/4" X 4" **NON-REVERSIBLE STEEL CUTTING EDGE** cuts and lifts hard packed snow and ice

TOUGHER THAN A N AD IAN INT **FR**











MEET THE REST OF THE ARCTIC POLY LINE





ARCTIC XHD

ARCTIC HDSSTE

ARCTIC HDVTE





WHY CHOOSE POLY?

Arctic's high density polyethylene moldboards combine the durable, slick characteristics of poly with advanced blade design mechanics to throw more of even the stickiest, wettest snow further and faster. This not only results in more snow being moved more quickly, it also minimizes forward resistance meaning decreased wear on power trains and increased fuel economy. **Contact your Arctic Dealer to** learn more about the high-tech, low-maintenance benefits of poly.



M200 SERIES HYDRAULIC POWER UNIT The M200 couples the newest in modular micro pump technology with a 12 volt, 3" motor, and a valve configuration similar to that used in our larger pumps. Operating pressure is set at 1500 psi and provides crossover relief at 2000 psi. The result is smooth, effortless operation from a compact pump that is compatible with all of our control systems.



MOUNTING KIT

The mounting frame, a smaller version of the full-size QUIK*LINK® units, stands on an adjustable support leg and houses the M200 pump in 3/8" thick laser cut plate (shown with optional lights).

ARCTIC LD-P SPECIFICATIONS

Plow Name	LD78-P	LD84-P
Length	78″	84"
Moldboard Height	18″	18″
Material	1/4" Poly	1/4" Poly
Plowing Width (Full Angle)	69 1/2"	75″
Complete Weight	*370 lbs	*380 lbs
Mounting Type	Detachable	Detachable
Removable Lights and Power Unit	Yes	Yes

OPTIONAL CONTROLLERS



TOUCHPAD The touchpad responds instantly to the touch of a finger. Used handheld or mounted with a Velcro strip, it allows you to alter the plow's angle in the float position.



JOYSTICK The joystick is mounted to the window opening in the driver-side door and allows you to alter the plow's angle in the float position.



* Weight does not include undercarriage

MINI-JOYSTICK This smaller version of the joystick is suitable for handheld use or can be mounted with a window bracket. It also allows you to alter the plow's angle in the float position.



HAND HELD

This ergonomic controller has 4 rubber-faced buttons, a float light in the middle and a curly cord. An automatic shut-off eliminates accidental use or drained batteries.

STANDARD CONTROLLER



CONTROL BOX Our standard control box, with two rocker switches - one for up and down, one for left and right - has proven to continue performing reliably over years of use.



THE ARCTIC SNOWPLOW YEAR WARRANY Actic snow removal equipment is fully guaranteed to be free defects for three years from atter of purchase and the plow's structural integrity is covered ounditions apply. Please ask or call 888 413 0019.

QUIK*LINK® is a registered trade-mark of Arctic Equipment Manufacturing Corporation. LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment.

OUGHER Λ **DAN** INT

Arctic Equipment Manufacturing Corporation

Toll Free 888 413 0019 www.arcticsnowplows.com