WINTER DOESN'T PLAY NICE, WHY SHOULD YOU? Built for full-size vehicles, the

Arctic HD-P is the workhorse of the fleet. This popular plow, like all of our poly plows, uses a combination of slick polyethylene skin and advanced blade design mechanics to initiate a rolling motion that throws even the stickiest, wettest snow faster and further. Decreased resistance means less wear on your vehicle's power train and increased fuel economy.

7 LASER-CUT, STEEL REINFORCING RIBS

back our frictionless poly moldboard with the strength of steel

4 TENSION SPRINGS keep the blade upright and offer

ample room for addition of a shock absorber kit, if desired

improved fuel economy

3/8" POLYETHYLENE MOLDBOARD throws snow further and faster resulting in less resistance and vehicle wear, and

HOT-DIPPED GALVANIZED STEEL FRAME

provides added resistance to abrasion, water and rust, making our plows virtually maintenance free

THREE 3/4" OPEN PINS

secure the blade to the quadrant and A-frame assembly, eliminating pin seizure, and easing pin replacement

6" DEFLECTOR

keeps snow down on the blade and away from the driver's windshield

CUTTING EDGE

DISH-SHAPED SKID SHOES improve surface clearance while

plowing forward











MEET THE REST OF THE ARCTIC POLY LINE



HARDENED HIGH CARBON STEEL

with top hole

bolt pattern

TOUGHER THAN A CANADIAN

ARCTIC LD ARCTIC

ARCTIC

ARCTIC XHD

ARCTIC

WHY CHOOSE POLY?

Arctic's high density polyethylene moldboards combine the durable, slick characteristics of poly with advanced blade design mechanics to throw more of even the stickiest, wettest snow further and faster. This not only results in more snow being moved more quickly, it also minimizes forward resistance – meaning decreased wear on power trains and increased fuel economy. Contact your Arctic Dealer to learn more about the high-tech,

low-maintenance benefits of poly.



M673 HYDRAULIC POWER UNIT

Arctic's electric, hydraulic outfront pumps are designed specifically for the quick response required by snowplow applications. The M673 uses a low-amperage draw motor combined with a high-flow pump operating at 2200 psi to give the operator fast plow response with low battery drain.



QUIK*LINK® II AND III MOUNTING SYSTEMS

Featuring an adjustable jack stand, our mounting systems allow you to remove the entire plow assembly as a single unit with the lift frame intact. QUIK*LINK® II uses mounting pins on either side of the system to easily attach and detach the plow from your vehicle. Arctic's QUIK*LINK® III system makes the already-simple mounting system even easier to use by replacing the two mounting pins with a simple single locking bar.

ARCTIC HD-P SPECIFICATIONS

Plow Name	HD90-P	HD96-P
Length	90"	96"
Moldboard Height	29"	29"
Material	3/8" Poly	3/8" Poly
Plowing Width (Full Angle)	78″	83"
Complete Weight	*631 lbs	*647 lbs
Mounting Type	Detachable	Detachable
Removable Lights and Power Unit	Yes	Yes

Weight does not include undercarriage

STANDARD CONTROLLER



CONTROL BOX

Our standard control box, with two rocker switches – one for up and down, one for left and right – has proven to continue performing reliably over years of use.

OPTIONAL CONTROLLERS



TOUCHPAD

The touchpad responds instantly to the touch of a finger. Used handheld or mounted with a Velcro strip, it allows you to alter the plow's angle in the float position.



JOYSTICK

The joystick is mounted to the window opening in the driver-side door and allows you to alter the plow's angle in the float position.



MINI-JOYSTICK

This smaller version of the joystick is suitable for handheld use or can be mounted with a window bracket. It also allows you to alter the plow's angle in the float position.



HAND HELD

This ergonomic controller has 4 rubber-faced buttons, a float light in the middle and a curly cord. An automatic shut-off eliminates accidental use or drained batteries.



QUIK*LINK® is a registered trade-mark of Arctic Equipment Manufacturing Corporation.

LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment.